

Unique Coats

Unique Coats

UV shield and Monsoon guard

Unique Coats

Wide shade options

Unique Coats

Bright and deep Colour

Wide shade options

Unique Coats

Colours with choice, softness, elegance, and Protection

Hygienic range

Easy to clean

Vibrant colours

Majestic looks

Complete coating range



Unique oats

COLOURS WITH **CHOICE,**
SOFTNESS,
ELEGANCE AND PROTECTION

Ind Industrial Exports (Brand : Unique Coats)

Coatings & Construction Chemical

Head Office : 53, A4C Janakpuri, New Delhi, Pincode - 110058

Works : E 66, Sardar Udyog Nagar, Sadar Estate, Ajwa Road, Vadodara-19.

Email : info@indianindustrialexporters.com **website :** www.uniquecoats.com, www.uniquecoats.net

emperor acrylic distemper

UNIQUE COATS

PRODUCT DESCRIPTION

Unique Emperor-Smooth Distemper (water washable) is water based acrylic interior wall distemper. It is water based hence non inflammable.

PRIMER FEATURES AND BENEFITS

Unique Emperor matches the quality level of the emulsions offering the range at very competitive price. It gives excellent matt finish which last for years. Its formulation ensures multiple shades retention and minimizing drying time. It is washable and most of the stains are removed by mild soap sponging.

SUBSTRATE SUITABILITY

Suitable for false ceilings, asbestos sheets, all types of plasters, concrete etc.

APPLICATION DETAILS

Coverage is around 14-19 sqmtrs/kg in single coat and 7-9 sqmtrs /kg in second coat.

Application Steps

- 1 Use 180 emery papers to sand surface.
- 2 Brush UC-INT-Pri one coat; leave it for 6-8 hours.
- 3 Apply UC -INT-Pri second coat , dry it for 6-8 hours.
- 4 Apply wall putty and leave it for drying for 4-6 hours.
- 5 Sand the wall with 180 paper.
- 6 Apply 1st coat of UC-INT-smooth Dist);leave it for 3-4 hours.
- 7 Apply 2nd coat of UC -INT-smooth Dist and last coat (if required)at an interval of 3-4 hours.

Recommended shelf life is 3 years from the date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

Packing size : 1 kg, 10 kg , 20 kg

emperor **acrylic** distemper



prime interior emulsion

UNIQUE COATS

PRODUCT DESCRIPTION

Unique Prime Emulsion is Water Based, smooth matt finished acrylic paint for interior special walls.

PRIMER FEATURES AND BENEFITS

Unique Prime Emulsion is a smart choice of having wonderful shades options at very especial price. Surface finish is matt but gives rich look to the walls. It gives stain resistance and option for extra deep colours for special walls Prime Emulsion gives excellent resistance against fungal growth, long lasting finish, dark shades options for distinguished featured wall.

SUBSTRATE SUITABILITY

Suitable for concrete, smooth plaster, asbestos sheets, etc.

APPLICATION DETAILS

Its first coat gives coverage of around 27 -32sqm/litre, while second coat 15-10 sqm/litre, on 40% dilution and can exceed depending on the surface smoothness.

Application steps:

- 1 Scrub the surface with 180 emery paper.
- 2 Apply diluted primer UC -INT -Pri for 6-8 hours.
- 3 Apply second coat of diluted primer UC -INT -Pri for 6-8 hours.
- 4 Apply wall putty and leave it for drying for 4-6 hours.
- 5 Again wipe with 180 paper.
- 6 Now finish with 1st coat of UC-INT-EMULSION and leave it for 3-4 hours.
- 7 Finally apply 2nd coat of UC-INT-EMULSION and third (if required) in an interval of 3-4 hours.

Recommended shelf life is 3 years from the date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

Packing size : 1 litre, 4 litre, 10 litre, 20 litre



prime
interior
emulsion

smoother exterior paint

UNIQUE COATS

PRODUCT DESCRIPTION

Smoother is water based economic exterior emulsion for humid climatic conditions.

PRIMER FEATURES AND BENEFITS

Smoother gives excellent resistance against fungal, algae or any other microorganism growth provides excellent matt finish with light and dark shades with excellent hiding.

Unique Smoother-EMUL (anti-fungal) is the great experience of the smoothness offered with protection formulae against weather extremes and algae-fungus detonation to the exterior walls.

SUBSTRATE SUITABILITY

Suitable for concrete, smooth plaster, asbestos sheets, etc.

APPLICATION DETAILS

Its first coat gives coverage of around 14-15sqm/litre, while second coat 9-10 sqm/litre, and can exceed depending on the surface smoothness.

Application Steps :

- 1 Scrub the surface with 180 emery paper.
- 2 Apply diluted primer UC - Exterior - Pri for 6-8 hours.
- 3 Apply second coat of diluted primer UC - Exterior - Pri for 6-8 hours.
- 4 Apply wall putty and leave it for drying for 4-6 hours.
- 5 Again wipe with 180 paper.
- 6 Now finish with 1st coat of UC - EXTERIOR EMULSION and leave it for 3-4 hours.
- 7 Finally apply 2nd coat of UC - EXTERIOR - EMULSION and third (if required) in an interval of 3-4 hours.

Recommended shelf life is 3 years from the date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

Packing size : 1 liter, 4 liter, 10 liter, 20 liter



smoother exterior paint

PRODUCT DESCRIPTION

Unique emperor emulsion is water based, smooth finished acrylic paint for interior walls.

PRIMER FEATURES AND BENEFITS

Unique emperor emulsion is a smart choice of having wonderful shades options at very especial price. Surface finish is matt and smooth. It is generally washable and most stains are removed by sponging with mild soap solution. Emperor emulsion gives excellent resistance against fungal growth, long lasting finish, dark shades options for distinguished featured wall.

SUBSTRATE SUITABILITY

Suitable for concrete, smooth plaster, asbestos sheets, etc.

APPLICATION DETAILS

Its first coat gives coverage of around 14-15sqm/litre, while second coat 9-10 sqm/litre, and can exceed depending on the surface smoothness.

Application Steps :

- 1 Scrub the surface with 180 emery paper.
- 2 Apply diluted primer UC -INT -Pri for 6-8 hours.
- 3 Apply second coat of diluted primer UC -INT -Pri for 6-8 hours.
- 4 Apply wall putty and leave it for drying for 4-6 hours.
- 5 Again wipe with 180 paper.
- 6 Now finish with 1st coat of UC-INT-EMULSION and leave it for 3-4 hours.
- 7 Finally apply 2nd coat of UC-INT-EMULSION and third (if required) in an interval of 3-4 hours.

Recommended shelf life is 3 years from the date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

Packing size : 1 liter, 10 liter, 20 liter



exterior **cement** primer

PRODUCT DESCRIPTION

Unique Coats Wall Primer is water based coating suitable for undercoat for exterior emulsions.

PRIMER FEATURES AND BENEFITS

UC-EXT Pri has good opacity and whiteness, therefore improves the appearance of the emulsion topcoats. It can be directly applied on the smooth plastered surface. It does not need water curing.

SUBSTRATE SUITABILITY

Suitable for exterior ceilings, asbestos sheets, concrete, cement plaster etc.

APPLICATION DETAILS

Unique exterior primer gives excellent coverage of around 12-14 sqmtr/litrs, second coat 6-7 sqm/liter. We recommend UC protect prior to the UC -Ext to increase the life of the building and coating.

Application Steps

Clear off the application surface from dust, grease, oil, fungus loose paint etc. with following steps.

- 1 Sand the surface with sand paper 80/100 thoroughly.
- 2 Wash it with water by coir brush.
- 3 Fill cracks and dents with white cement and fine sand (1:3)
- 4 Apply UC protect-EXT-Pri, leave it for 4 (24 hrs for excellent result).
- 5 Allow it to dry.
- 6 Apply UC-EXT-Pri two coats with an interval of 4 hrs in between.

Recommended shelf life is 3 years from the date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

Packing size : 1 liter, 10 liter, 20 liter

interior **cement** primer

PRODUCT DESCRIPTION

Unique Coats Wall Primer is water based coating suitable for undercoat for Interior plastic emulsions and distemper.

PRIMER FEATURES AND BENEFITS

UC-INTPriUnique interior primer is water thinable and used for interior base coating of the wall. Its excellent formulation makes it anti -anti fungal and resistant against any micro organism growth.

SUBSTRATE SUITABILITY

Suitable for asbestos sheets, concrete, cement plaster etc.

APPLICATION DETAILS

Unique interior primer gives excellent coverage of around 12-14 sqmtr/litrs, second coat 6-7 sqm/liter. Recommended shelf life is 3 years from the date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

2 coats for repainting, 3 coats for new surface

Application steps

- 1 Clear the wall with emery paper 180
- 2 Apply 1st coat of primer, keep it for drying for 3-4 hrs.
- 3 Apply putty to cover dents and cracks and leave it for drying for 4-6 hrs.
- 4 Use sand emery paper 180 and wipe clean the wall.
- 5 Apply 2- coats of UC-INT-2Pri at an interval of 3-4 hrs.



vibrant exterior emulsion

PRODUCT DESCRIPTION

Vibrant is a water based exterior emulsion for giving durable and smooth finish to the wall.

PRIMER FEATURES AND BENEFITS

Vibrant is exterior emulsion paint with excellent resistance against weather extremes, algae, fungus any microorganism and UV degradation.

SUBSTRATE SUITABILITY

Suitable for concrete, smooth plaster and asbestos sheets.

APPLICATION DETAILS

Its first coat gives coverage of around 14-15sqm/litre, while second coat 9-10 sqm/litre, and can exceed depending on the surface smoothness.

Application Steps :

- 1 Scrub the surface with 180 emery paper.
- 2 Apply diluted primer UC - Exterior - Pri for 6-8 hours.
- 3 Apply second coat of diluted primer UC - Exterior - Pri for 6-8 hours.
- 4 Apply wall putty and leave it for drying for 4-6 hours.
- 5 Again wipe with 180 paper.
- 6 Now finish with 1st coat of UC - EXTERIOR EMULSION and leave it for 3-4 hours.
- 7 Finally apply 2nd coat of UC - EXTERIOR - EMULSION and third (if required) in an interval of 3-4 hours.

Recommended shelf life is 3 years from the date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

Packing size : 1 liter, 4 liter, 10 liter, 20 liter

vibrant exterior emulsion



UC protect exterior interior primer

UNIQUE COATS

UC protect exterior/interior primer

PRODUCT DESCRIPTION

This is an essential base coat for exterior/interior walls, required to keep walls safe from salt deposition, anti-bacterial, ant-fungal growths. UC protect ensure walls secure for years.

APPLICATION DETAILS

- 1 Strongly reduce absorption of the substrate,
- 2 The entry of rain into the substrates through defects in the coating is avoided.
- 3 Deactivation of cracks in the substrate.
- 4 Dirt agglomeration is avoided.
- 5 Humidity creeping is avoided
- 6 Neither water nor water soluble aggressive salts or base may concentrate in direct vicinity of the coating.
- 7 Loose particle of the sand substrate are bound.
- 8 Coverage of 100-125 sq.ft./litr. in single coat.

Recommended shelf life is 6 months once container is opened.

This product is already tested and admired in Gujarat, especially in Kutch region.

Ind Industrial Exports

Coatings & Construction Chemical Works : E 66, Sardar Udyog Nagar, Sardar Estate, Ajwa Road, Vadodara-19, Gujarat, (India)

Ph. : 098104 46156

Email : info@indianindustrialexporters.com



uc protect exterior interior primer

UNIQUE COATS

PRODUCT DESCRIPTION

This is an essential base coat for exterior/interior walls, required to keep walls safe from salt deposition, anti-bacterial, ant-fungal growths. UC protect ensure walls secure for years.

APPLICATION DETAILS

- 1 Strongly reduce absorption of the substrate,
- 2 The entry of rain into the substrates through defects in the coating is avoided.
- 3 Deactivation of cracks in the substrate.
- 4 Dirt agglomeration is avoided.
- 5 Humidity creeping is avoided
- 6 Neither water nor water soluble aggressive salts or base may concentrate in direct vicinity of the coating.
- 7 Loose particle of the sand substrate are bound.
- 8 Coverage of 100-125 sq.ft./litr. in single coat.

Recommended shelf life is 6 months once container is opened.

This product is already tested and admired in Gujarat, especially in Kutch region.

Ind Industrial Exports

Coatings & Construction Chemical Works : E 66, Sardar Udyog Nagar, Sardar Estate, Ajwa Road, Vadodara-19, Gujarat, (India)
Ph. : 098104 46156, 95749 01333
Email : info@indianindustrialexporters.com



uc protect exterior/interior primer